

KROY

K4700 series:

- K4710 - 200 dpi
- K4730 - 300 dpi
- K4760 - 600 dpi

Zebra printer emulation
built in



Introducing the all new range of industrial printers from Kroy

Never before have so many standard features been packed into a label printer at such an affordable price.

At print speeds up to 12 inches per second the K4710 is the fastest printer in the K4700 series line-up. By combining high speeds with the K4700 series durable die-cast aluminium frame, the K4710 is ideal for your mission critical printing applications, either on-demand or in batches.

Where a higher print resolution is required the K4730 with its 300 dpi print head offers print speeds at up to 8 inches per second with crisp, sharp print quality.

The K4760 - 600 dpi printer with speeds up to 4 inches per second gives the highest print resolution. Wherever you need to print labels with graphics and or high density text the K4760 will meet the challenge.

Designed to give excellent reliability in industrial environments, with a 2 year limited warranty on the printer and 25 kilometre /12 month warranty on the print head, the K4700 series metal cased printers are fit for the most demanding environments.

Kroy Europe Ltd, are a **3M** Accredited Converter (ACE) and carry an extensive range of labels, speciality materials, printer ribbons, spares and accessories.



KROY K4652/53, K4710/30/60

Printer model	Industrial model			Economy model	
	K4710	K4730	K4760	K4652NB	K4653NB
Resolution	203 DPI	300 DPI	600 DPI	203 DPI	300 DPI
Printing method	Thermal Transfer and/or Direct Thermal				
Max. print speed	Up to 12 ips	Up to 8 ips	Up to 4 ips	Up to 8 ips	Up to 6 ips
Max. print width		104 mm (4.09")		108 mm (4.25")	104 mm (4.09")
Max. print length	4064 mm (160")	1854.2 mm (73")	1016 mm (40")	2286 mm (90")	1016 mm (40")
Enclosure	Die-cast aluminum base and frame.			Metal cover with large clear media view window	
Physical dimension	270 mm (W) x 308 mm (H) x 505 mm (D) or 10.63" (W) x 12.13" (H) x 19.88" (D)				
Weight	15 kg				
Label roll capacity	208.3 mm (8.2") OD				
Ribbon	600 meter long, 1" core (ink coated outside or inside)				
Ribbon width	25.4 mm ~ 114.3 mm (1"~4.5")				
Processor	32-bit RISC CPU				
Memory	<ul style="list-style-type: none"> ● 8MB Flash memory ● 32MB SDRAM ● SD Flash memory card slot for Flash memory expansion 			<ul style="list-style-type: none"> ● 4MB Flash memory ● 8MB SDRAM 	
Power	<ul style="list-style-type: none"> ● RS-232C (2400 - 115200 bps) ● Centronics (SPP mode) ● USB 2.0 client (full speed) ● PS/2 keyboard interface ● Internal Ethernet print server 			<ul style="list-style-type: none"> ● RS-232C (2400- 115200 bps) ● Centronics (SPP mode) ● USB 2.0 client (full speed) 	
LCD display	Graphic type, 128 x 64 pixel, with back light				
Operation switch, button	1 power switch, 6 operation buttons				
Sensors	<ul style="list-style-type: none"> ● Position adjustable transmissive/reflective sensor ● Ribbon end sensor ● Head open sensor 				
Real time clock	Standard				
Internal fonts	<ul style="list-style-type: none"> ● 8 alpha-numeric bitmap fonts ● Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font 				
Bar code	1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D bar code PDF-417, Maxicode, DataMatrix, QR code				
Font & barcode rotation	0, 90, 180, 270 degree				
Command set	TSPL-EZ™				
Media type	Continuous, die-cut, fan-fold, tag, notched, black mark, perforated, care label				
Media width	25.4~118 mm (1" ~ 4.6")				
Media thickness	0.06~0.30 mm (2.3~11.8 mil), 300g/m ²				
Media core diameter	25.4~76.2 mm (1"~3")				
Label length	5~4064 mm (0.20"~160")	5~1854.2 mm (0.20"~73")	5~1016 mm (0.20"~40")	5~2286 mm (0.20"~90")	5~1016 mm (0.20"~40")
Environment condition	Operation: 5~40 °C, 20~85% non-condensing Storage: -5~60 °C, 5~90% non-condensing				
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, UL, CUL, TUV/GS, CCC, CB				
Environmental concern	Comply with RoHS, WEEE				
Accessories	<ul style="list-style-type: none"> ● Labelling software CD disk ● Quick start guide 			<ul style="list-style-type: none"> ● USB cable ● Power cord 	
Limited warranty	<ul style="list-style-type: none"> ● Print head: 1 million inches (25 km) or 12 months which comes first since delivery from TSC ● Printer: 2 years 			Platen: 50 km	
Factory options	<ul style="list-style-type: none"> ● RFID ready printer ● Peel-off kit (include internal rewind & peel off module) ● Internal rewinding kit (include internal rewind & label redirect front panel) ● Applicator I/O interface 			<ul style="list-style-type: none"> ● RFID ready printer ● Peel-off kit (include internal rewind & peel off module) ● Internal rewinding kit (include internal rewind & label redirect front panel) 	
Dealer options	N/A			Multi-interface board : <ul style="list-style-type: none"> ● Configuration 1: Internal Ethernet print server + PS/2 keyboard interface + SD flash memory card slot ● Configuration 2: Applicator I/O interface + Internal Ethernet print server + PS/2 keyboard interface + SD flash memory card slot 	
User options	<ul style="list-style-type: none"> ● Regular cutter ● Heavy duty cutter ● External wireless (802.11b/g) print server 			<ul style="list-style-type: none"> ● Bluetooth module ● KP-200 series keyboard ● KU-007 Plus programmable smart keyboard 	



Specifications are subject to change without notice.

Kroy Europe Ltd
 Unit 2, 14 Commercial Road,
 Reading, Berkshire RG2 0QJ U.K.

Tel: +44 (0)118 9865200
 Fax: +44 (0)118 9865205
 Email: info@kroyeurope.com
 www.kroyeurope.com

